

RECEIVED  
CENTRAL FAX CENTER

APR 16 2008

2003P12731WOUS  
Marcus BACHMANN *et al.*  
Appl. No.: 10/566,171

## AMENDMENTS TO THE CLAIMS

The text of all pending claims is set forth below. The following listing of claims will replace all prior versions, and listings, of claims in the application.

Listing of Claims

1. (cancelled)
2. (cancelled)
3. (currently amended) The device according to ~~claim 1~~ Claim 16, wherein the nozzle holder in ~~the a~~ region of the washing nozzle, ~~has a large~~ has an opening having a diameter that is larger than in comparison with a diameter of a washing-fluid jet which ~~can~~ is to be generated by the washing nozzle.
4. (currently amended) The device according to ~~claim 1~~ Claim 16, wherein the nozzle holder has a chamber ~~which is arranged~~ immediately upstream of the insert ~~of the washing nozzle~~, as seen in ~~the a~~ direction of flow, and, ~~in order~~ configured to connect a washing-agent supply to the washing nozzle, ~~is formed over the entire pivoting range thereof.~~
5. (currently amended) The device according to ~~claim 1~~ Claim 16, wherein the nozzle holder is in mushroom form and, on ~~the an~~ underside of ~~its a~~ head region, has a latching means ~~which is provided for connecting it the nozzle holder~~ to a bodywork panel.
6. (currently amended) The device according to ~~claim 1~~ Claim 16, wherein the insert ~~or the washing nozzle is formed cylindrically or conically and has means which are is~~ accessible from outside the nozzle holder and ~~are intended for the~~ configured for attachment of a turning tool.

2003P12731WOUS  
Marcus BACHMANN *et al.*  
Appl. No.: 10/566,171

7. (currently amended) The device according to ~~claim 1~~Claim 16, wherein the cutout ~~which generates the washing fluid jet~~ is a bore.

8. (cancelled).

9. (currently amended) The device according to ~~claim~~Claim 7, wherein the bore tapers in a downstream direction in one of a continuously or incontinuous and a step-like manner downstream.

10. (currently amended) The device according to ~~claim 1~~Claim 16, wherein the ~~connection of the half cylinder or half cone~~ half-cylinders are connected via a film hinge.

11. (cancelled).

12. (currently amended) The device according to ~~claim~~Claim 10, wherein the cutout ~~which generates the washing fluid jet~~ is arranged in ~~the a~~ region of at least one section plane of a half-cylinder ~~or half cone.~~

13. (currently amended) The device according to ~~claim~~Claim 10, wherein the cutout ~~which generates the washing fluid jet~~ is arranged in ~~the a~~ region of a section plane of a half-cylinder ~~or half cone~~, and ~~in that~~wherein the section planes plane of the second half-cylinder ~~or half cone~~ is designed as a sealing surface.

14. (cancelled)

15. (cancelled)

16. (new) A device for cleaning a window or headlamp lens of a motor vehicle, comprising:

2003P12731WOUS  
Marcus BACHMANN *et al.*  
Appl. No. 10/566,171

a nozzle holder;  
a washing nozzle; and  
an insert arranged in the nozzle holder and configured to retain the washing nozzle within the nozzle holder, wherein the insert is rotatable with respect to the nozzle holder so that an angle of inclination of the washing nozzle is adjustable with respect to the nozzle holder,  
wherein the insert has a cutout configured to generate a washing-fluid jet,  
and  
wherein the insert is divided along a longitudinal axis into two substantial half-cylinders, each half-cylinder having a section plane, wherein the half-cylinders are pivotably connected to one another at a longitudinal edge of their section planes to form a cylinder when lying one upon the other by way of their section planes.

17. (new) A device for cleaning a window or headlamp lens of a motor vehicle, comprising:

a nozzle holder; and  
an insert arranged in the nozzle holder and configured as a washing nozzle, wherein the insert is rotatable with respect to the nozzle holder so that an angle of inclination of the washing nozzle is adjustable with respect to the nozzle holder,  
wherein the insert has a cutout configured to generate a washing-fluid jet,  
and  
wherein the insert is divided along a longitudinal axis into two substantial half-cylinders, each half-cylinder having a section plane, wherein the half-cylinders are pivotably connected to one another at a longitudinal edge of their section planes to form a cylinder when lying one upon the other by way of their section planes.

18. (currently amended) The device according to Claim 17, wherein the cutout is a fluidic structure configured to generate an oscillating washing-fluid jet.